

Order number: 01 276 06 99

SCHELL electronic wash basin mixer MODUS E HD-M

(high pressure mixed water)
vandal-resistant valve body
battery operation 9 V, incl. 9 V alkaline battery electronic module with battery level indicator

Scope of delivery:

- infrared sensor single hole tap
- electronic module with program for adjustment control and part time stagnation flush program (permanent flush 20 s/24 h flush)
- cartridge solenoid valve 6 V
- 2 flexible hoses Clean-Fix S G3/8 int. thread x 380 mm with integrated backflow preventer (BP, DIN EN 1717: EB)
- 2 prefilters
- flow regulator
- wash basin mounting accessories

Field of application / Technical data:

- flow volume: max. 5 l/min independent of pressure
- flow pressure: 1 - 5 bar
- Max. resting pressure 8 bar
- Water temperature max. 70°C (80°C permissible for 10 min./day)

Details:

- Material: housing out of brass conform German drinking water regulation, cover of battery compartment out of plastic
- Test Mark: P-IX 28338/IO, Belgaqua
- Surface: chrome
- Weight: 1.79 kg/pc.
- Packaging unit: 1

Versions:

mains operation 12 V, ca. 430 mm connection cable Order No.: [01 274 06 99](#)
with plug, protection category IP 65, incl. transformer
plug, 100 - 240 V, 50 - 60 Hz, chrome, PU 1, W: 1.66
kg/pc.

Recommended associated item:

| | | | |
|---|------------|------------------------------|----|
| flow regulator, UNIVERSAL, theft safe | Order No.: | 02 121 06 99 | |
| angle valve thermostat | Order No.: | 09 406 06 99 | or |
| regulating angle valve with normal filter with ASAG easy | Order No.: | 05 428 06 99 | or |
| regulating angle valve with normal filter without ASAG easy | Order No.: | 05 429 06 99 | or |
| sampling angle valve | Order No.: | 03 835 06 99 | |
| Pressure Balance Valve PBV | Order No.: | 06 558 12 99 | |
| extension cable 1,5 m | Order No.: | 01 550 00 99 | |

