

TECHNICAL DATASHEET

ABRAP

Denomination: HEAVY-DUTY METAL CLAMPS

Codes: AB-RI, AB-RE, AB-RA, AB-IA, AB-IR, AB-GA, AB-PE, AB-M8, ABDE, AB-DP, AB-ZI, AB-SA, AB-GP

Reference: FT ABRAP-en

Date: 07/03/18


Revision: 5

Page: 3 of 15

2. INSTALLATION DATA

2.1 AB-RI

Reinforced isophonic pipe clamp M8+M10



Zinc-plated Ventilation pipe Steel pipe Copper pipe PVC pipe

Installation data

Code	Size [mm]	$\varnothing D$ (mm)	$\varnothing D$ (")	A x B (mm)	Maximum load recommended (kg)
ABRI018	18	15 - 19	3/8"	19x1.8	150
ABRI022	22	20 - 25	1/2"	19x1.8	150
ABRI028	28	26 - 30	5/8"	19x1.8	150
ABRI035	35	32 - 36	1"	19x1.8	150
ABRI040	40	38 - 43	1 1/4"	19x1.8	150
ABRI048	48	47 - 51	1 1/2"	19x1.8	150
ABRI054	54	53 - 56	-	19x1.8	150
ABRI060	60	60 - 64	2"	19x1.8	150
ABRI070	70	68 - 72	-	19x1.8	150
ABRI075	75	75 - 80	2 1/2"	19x1.8	150
ABRI083	83	81 - 86	-	19x1.8	150
ABRI090	90	87 - 92	3"	19x1.8	150
ABRI100	100	99 - 105	3 1/2"	19x1.8	150
ABRI110	110	107 - 112	-	19x2,3	200
ABRI115	115	113 - 118	4"	19x2,3	200
ABRI125	125	125 - 130	4 1/2"	19x2,3	200
ABRI133	133	132 - 137	-	19x2,3	200
ABRI140	140	138 - 142	5"	19x2,3	200
ABRI150	150	148 - 152	-	19x2,3	200
ABRI160	160	159 - 166	6"	19x2,3	200
ABRI180	180	179 - 184	8"	19x2,3	200
ABRI200	200	199 - 212	-	19x2,3	200
ABRI220	220	215 - 226	-	19x2,3	200
ABRI250	250	245 - 254	-	19x2,3	200
ABRI300	300	299 - 304	-	19x2,3	200
ABRI315	315	314 - 319	-	19x2,3	200
ABRI355	355	354 - 359	-	19x2,3	200
ABRI400	400	399 - 404	-	19x2,3	200
ABRI450	450	449 - 454	-	19x2,3	200
ABRI500	500	499 - 504	-	19x2,3	200
ABRI560	560	555 - 561	-	19x2,3	200
ABRI600	600	599 - 604	-	19x2,3	200
ABRI630	630	625 - 631	-	19x2,3	200
ABRI710	710	705 - 711	-	19x2,3	200
ABRI800	800	799 - 804	-	19x2,3	200
ABRI900	900	899 - 904	-	19x2,3	200
ABRI910	1000	999 - 1.004	-	19x2,3	200
ABRI911	1120	1.115 - 1.121	-	19x2,3	200
ABRI912	1250	1.245 - 1.251	-	19x2,3	200

- Pipes from $\varnothing 18$ to $\varnothing 1250$ mm.
- Surface coating: electrolytic zinc plated, coating >5 microns.
- Isophonic, EPDM rubber for insulation, noise and vibration reduction.
- According to Technical Building Code, TBC, Basic reports HS and HR.
- Steel profile de 1.8 ± 2.3 mm thickness.
- Side screws with plastic washer to avoid losses.
- Reinforced.
- Welded nut of M8+M10.
- Suitable for steel, plastic, copper and ventilation pipes.
- Recommended for water supply installations (HSW and CW), drain networks (sanitation), thermal installations (heating, air-conditioning and ventilation systems), compressed air, gas installations, etc.
- Service temperature: -30°C ÷ +120°C.
- Large sizes available for ventilation pipes.

DRAWING

