



### Osnovne informacije

Grupa proizvoda	Modicon Momentum platforma za automatizaciju
Tip proizvoda ili komponente	Adapter za M1/M1E procesora
Koncept	Transparent Ready
Nivo ili klasa	Klasa B10
Namena softvera	Concept V2.6 Modsoft >= V2.5 ProWORX NxT V2.0 ProWORX 32
Protokol komunikacionog porta	Ethernet
Ime procesora	X 86 arhitektura (INTEL, AMD) IEC executive
Frekvencija sata	50 MHz

### Dopunske informacije

Veb servisi	Rack viewer (pregled reka) Softverski alat za učitavanje veb stranica Učitavanje veb stranica Editor podataka
Ethernet servis	I/O skeniranje Modbus TCP komunikacija
Kapacitet i/o	8192 I/8192 O
Tip memorije	1 MB fleš 544 kB RAM
Opis memorije	Programska memorija 18 kB LL984 Programska memorija 200 kB IEC Podaci 24 kB
Materijal	Leksan
Dužina reči	16 bit
[us] nazivni napon	5.0 V DC +/-5 %
Napajanje	Putem Momentum I/O baze
Tacno vreme za 1 k instrukcija	1 ms
Kapacitet i/o registara procesora	26048 I/26048 O
I/o kapacitet procesora	8192 bita maksimalno
I/o reči po čvoru	128 I/O Concept 80 I/O ProWORX
Broj portova	1 I/O bus 1 Ethernet
Označavanje	CE
Masa proizvoda	0,042 kg

### Okruženje

Tretman zaštite	TC
Temperatura okoline za rad uređaja	0...60 °C
Temperatura okoline za skladištenje	-40...85 °C
Relativna vlažnost	5...96 % bez kondenzacije
Nadmorska visina za rad	2000 m
Otpornost na udare	<= 15 gn vršno 11 milisekundi ubrzanje polovine sinusne periode

Informacije navedene u ovoj dokumentaciji predstavljaju opšti opis odnosno tehničke karakteristike performansi proizvoda. Dokumentacija nije namenjena da bude zamena za niti se može koristiti za određivanje prikladnosti i pouzdanosti proizvoda za specifičnu krajnju primenu. Dužnost je korisnika odnosno integratora da izvrši primerenu i sveobuhvatnu analizu rizika, procenu i proveru proizvoda u pogledu odgovarajuće specifične primene ili načina korišćenja. Ni Schneider Electric Industries SAS ni njegova poveznata ili zavisna društva neće snositi odgovornost za zloupotrebu ovdenevidenih informacija.

Otpornost vibracija	1 gn 0.75 mm d.a
Sertifikacija proizvoda	UL Nema tip 250 CUL FM klasa 1 odeljak 2

## Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6,0 cm
Package 1 Width	18,0 cm
Package 1 Length	26,0 cm
Package 1 Weight	197,0 g
Unit Type of Package 2	S04
Number of Units in Package 2	20
Package 2 Height	30,0 cm
Package 2 Width	40,0 cm
Package 2 Length	60,0 cm
Package 2 Weight	4,84 kg
Unit Type of Package 3	S02
Number of Units in Package 3	4
Package 3 Height	15,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	1,122 kg

## Ugovorna garancija

Garancija	18 meseci
-----------	-----------