



Osnovne informacije

Range of product	Acti9
Kratko ime uređaja	iATLc+c
Tip proizvoda ili komponente	Pomoćni blok - centralizovano upravljanje na više nivoa
Napon upravljačkog kola	24...240 V AC 50/60 Hz impuls

Dopunske informacije

[ui] nazivni napon izolacije	440 V
[uimp] nazivni podnosivi impulsni napon	4 kV
Tip daljinskog upravljanja	2 ulaza za prekidač
Način montiranja	Fiksno
Nosači za montažu	DIN šina
9 mm redovi	2
Visina	86 mm
Širina	18 mm
Dubina	71 mm
Boja	Bela
Povezivanje - priključci	Tunelski priključci kabl 0,5...4 mm ² - krutost kabla: kruti Tunelski priključci kabl 0,5...4 mm ² - krutost kabla: kruti - sa kablovskim završetkom Tunelski priključci kabl 1...4 mm ² - krutost kabla: fleksibilni Tunelski priključci kabl 1...4 mm ² - krutost kabla: fleksibilni - sa kablovskim završetkom
Dužina ogoljenog dela žice	11 mm
Moment pritezanja	1 N.m
Kompatibilnost grupe proizvoda	Acti 9 (Acti 9 iTL) iTLc Acti 9 (Acti 9 iTL) iATLc Acti 9 (Acti 9 iTL) iATLc+s

Okruženje

Kategorija prenapona	III
Ip stepen zaštite	IP20 conforming to IEC 60529
Tropikalizacija	2
Relativna vlažnost	95 % pri 55 °C
Temperatura okoline za rad uređaja	-20...50 °C
Temperatura okoline za skladištenje	-40...70 °C
Standardi	EN/IEC 60669-2-2

Informacije navedene u ovoj dokumentaciji predstavljaju opšti opis odnosno tehničke karakteristike performansi proizvoda. Dokumentacija nije namenjena da bude zamena za niti se može koristiti za određivanje prikladnosti i pouzdanosti proizvoda za specifičnu krajnju primenu. Dužnost je korisnika odnosno integratora da izvrši primerenu i sveobuhvatnu analizu rizika, procenu i proveru proizvoda u pogledu odgovarajuće specifične primene ili načina korišćenja. Ni Schneider Electric Industries SAS ni njegova povezana ili zavisna društva neće snositi odgovornost za zloupotrebu ovenavedenih informacija.

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2,9 cm
Package 1 Width	8,0 cm
Package 1 Length	9,5 cm
Package 1 Weight	75,0 g
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Height	30,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm
Package 2 Weight	6,288 kg
Unit Type of Package 3	BB1
Number of Units in Package 3	8
Package 3 Height	8,5 cm
Package 3 Width	10,0 cm
Package 3 Length	26,5 cm
Package 3 Weight	640,0 g

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	 REACH Deklaracija
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Učinak u vezi sa sadržajem halogena	Proizvod sa plastičnim delovima bez halogena

Ugovorna garancija

Garancija	18 meseci
-----------	-----------