



Osnovne informacije

Range of product	Acti9
Ime proizvoda	Acti 9 iPB
Tip proizvoda ili komponente	Taster
Kratko ime uređaja	iPB
Standardi	IEC 60669-1 IEC 60947-5-1

Dopunske informacije

Tip kontakata i sastav	1 NO + 1 NC
[ie] nazivna struja	20 A
[ue] nazivni napon	250 V AC
Način upravljanja	1 taster siva
Način montiranja	Fiksno
Nosači za montažu	35 mm simetrična DIN šina
Razvodni blok češljaste sabirnice	Gornji: Clario Gornji: Libro Gornji: ProDis
9 mm redovi	2
Visina	82 mm
Širina	18 mm
Dubina	71,5 mm
Boja	Bela
Električna trajnost	AC-22: 30000 ciklusa AC 50/60 Hz
Povezivanje - priključci	Veći tunelski priključak1 kabl(ovi) 0,5 mm ² kruti Veći tunelski priključak1 kabl(ovi) 0,5 mm ² fleksibilni Veći tunelski priključak1 kabl(ovi) 0,5 mm ² fleksibilni sa kablovskim završetkom Veći tunelski priključak2 kabl(ovi) 2,5 mm ² kruti Veći tunelski priključak2 kabl(ovi) 2,5 mm ² fleksibilni Veći tunelski priključak2 kabl(ovi) 2,5 mm ² fleksibilni sa kablovskim završetkom
Dužina ogoljenog dela žice	9 mm
Moment pritezanja	1 N.m

Okruženje

Tropikalizacija	2
Relativna vlažnost	95 % pri 55 °C
Temperatura okoline za rad uređaja	-35...70 °C
Temperatura okoline za skladištenje	-40...80 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8,5 cm
Package 1 Width	2,0 cm
Package 1 Length	8,0 cm

Package 1 Weight	44,0 g
Unit Type of Package 2	S03
Number of Units in Package 2	108
Package 2 Height	30,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm
Package 2 Weight	5,776 kg
Unit Type of Package 3	BB1
Number of Units in Package 3	12
Package 3 Height	8,0 cm
Package 3 Width	10,0 cm
Package 3 Length	23,0 cm
Package 3 Weight	587,0 g

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------