



Osnovne informacije

Range of product	Acti9
Ime proizvoda	Acti 9 iIL
Tip proizvoda ili komponente	Modularna signalna lampica
Kratko ime uređaja	iIL
[us] nazivni napon	12...48 V AC pri 50/60 Hz 12...48 V DC

Dopunske informacije

Indicator light	1 LED žuta, 100000 sati 0,3 W)
Način montiranja	Fiksno
Nosači za montažu	Simetričnu DIN šinu
Razvodni blok češljaste sabirnice	Gornji: ProDis
9 mm redovi	2
Visina	82 mm
Širina	18 mm
Dubina	69,5 mm
Boja	Bela (RAL 9003)
Pomoćni priključni blok	Tunel klema 1 kabl(ovi) kruti 0,5 mm ² Tunel klema 2 kabl(ovi) kruti 2,5 mm ² Tunel klema 1 kabl(ovi) fleksibilni 0,5 mm ² Tunel klema 2 kabl(ovi) fleksibilni 2,5 mm ² Tunel klema 2 kabl(ovi) fleksibilni sa kablovskim završetkom 2,5 mm ²
Dužina ogoljenog dela žice	9 mm
Moment pritezanja	1 N.m

Okruženje

Standardi	IEC 60947-5-1
Ip stepen zaštite	IP2 IPxx B
Stepen zaprljanosti	3
Tropikalizacija	2
Relativna vlažnost	95 % pri 55 °C
Temperatura okoline za rad uređaja	-35...70 °C
Temperatura okoline za skladištenje	-40...80 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1,7 cm
Package 1 Width	6,8 cm
Package 1 Length	9,0 cm
Package 1 Weight	40,0 g
Unit Type of Package 2	S03

Number of Units in Package 2	108
Package 2 Height	30,0 cm
Package 2 Width	30,0 cm
Package 2 Length	40,0 cm
Package 2 Weight	5,377 kg
Unit Type of Package 3	BB1
Number of Units in Package 3	12
Package 3 Height	9,8 cm
Package 3 Width	8,0 cm
Package 3 Length	23,2 cm
Package 3 Weight	539,0 g

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	REACH Deklaracija
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.
Učinak u vezi sa sadržajem halogena	Proizvod sa plastičnim delovima i kablovima bez halogena

Ugovorna garancija

Garancija	18 meseci
-----------	-----------