



Osnovne informacije

Tip proizvoda ili komponente	Standardni radni kondenzator
Mrežna frekvencija	50/60 Hz
Ime serije	EasyLogic PFC Capacitor
Sastav harmonika mreže	<= 10 %
Electrical parameters	18,1 Kvar 380 V 50 Hz 21,7 Kvar 380 V 60 Hz 20 Kvar 400 V 50 Hz 24 Kvar 400 V 60 Hz 21,5 Kvar 415 V 50 Hz 25,8 kvar 415 V 60 Hz
Maksimalni dopustivi napon	1.1 x Un (8 časova tokom 24 časa)
Continuous overcurrent capacity	1.5 x In
Nazivni napon	380...415 V AC 50/60 Hz

Dopunske informacije

Dielektrični gubici	< 0.2 W/kvar
Snaga gubitaka	< 0.5 W/kVAr
Tolerancija kapacitivnosti	- 5 % do 10 %
Test napona	2.15 x Un AC između priključaka za 10 s <= 660 V - 3 kV AC između priključka i kućišta za 10 s >= 660 V - 6 kV AC između priključka i kućišta za 10 s
Udarne struja	200 x In
Maksimalni broj preklapanja po godini	5000
Servisni vek u časovima	100000 sati
Dielektrični materijal	Metalizirani polipropilenski sloj sa Zn/Al legurom,
Materijal punjenja	Ne PCB meka PUR smola Biorazgradiv
Tip instalacije	Instalacija u zatvorenom
Povezivanje - priključci	ClampTite priključak
Način montiranja	Vertikalno
Prečnik	90 mm
Visina	308 mm
Masa proizvoda	2,3 kg

Okruženje

Standardi	IEC 60831-2 IEC 60831-1
Ip stepen zaštite	IP20
Nadmorska visina za rad	2000 m
Temperaturna klasa	D
Temperatura okoline za rad	-25...55 °C
Relativna vlažnost	95 %

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12,749 cm
Package 1 Width	13,529 cm
Package 1 Length	36,4 cm
Package 1 Weight	2,27 kg
Unit Type of Package 2	P06
Number of Units in Package 2	32
Package 2 Height	60,0 cm
Package 2 Width	60,0 cm
Package 2 Length	80,0 cm
Package 2 Weight	86,3 kg
Unit Type of Package 3	S04
Number of Units in Package 3	8
Package 3 Height	30,0 cm
Package 3 Width	40,0 cm
Package 3 Length	60,0 cm
Package 3 Weight	19,33 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Profil cirkularnosti	Informacije O Kraju Radnog Veka
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 months
-----------	-----------