



Osnovne informacije

Seriya	Asfora
Tip proizvoda ili komponente	Utičnica
Opis standarda utičnice	Uzemljenje sa strane
Konfiguracija polova utičnice	2P + E sa zaštitom
Prezentacija uređaja	Kompletan proizvod
Dodatne informacije	Poklopac i zaštita
Nijansa boje	Bela
Tip pakovanja	Pakovanje u kesicama

Dopunske informacije

Broj utičnica	1
Montaža uređaja	Ugradno
Opseg snage	3680 W
Nazivna struja	16 A pri 250 V AC
Povezivanje - priključci	Vijčani priključci
Broj kablova	2 kabl(ovi) 2,5 mm ²
Krutost kabla	Fleksibilni Krući Jednožični višezični
Dužina ogoljenog dela žice	13,0 mm
Materijal	ABS (akrilonitril-butadien-stiren): dekorativni ram ABS + PC: centralna pločica ABS (akrilonitril-butadien-stiren): poklopac
Završna obrada	Sjajno
Provodni materijal	Bakar
Način fiksiranja	Zavrtnji ili kukice 51...69 mm
Visina	83 mm
Širina	83 mm
Dubina	48 mm
Projektovana dubina	17 mm
Količina po setu	1
Masa proizvoda	0,104 kg

Okruženje

Standardi	IEC 60884-1
Sertifikacija proizvoda	TSE VDE Aenor
Ip stepen zaštite	IP44

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,5 cm
Package 1 Width	8,0 cm
Package 1 Length	8,0 cm
Package 1 Weight	105,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9,5 cm
Package 2 Width	18,5 cm
Package 2 Length	27,5 cm
Package 2 Weight	1,126 kg
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30,0 cm
Package 3 Width	40,0 cm
Package 3 Length	60,0 cm
Package 3 Weight	14,062 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------