



Osnovne informacije

Grupa proizvoda	TeSys TeSys Deca
Kratko ime uređaja	LAD4
Tip proizvoda ili komponente	Prigušivač
Kompatibilnost proizvoda	3P LC1D40A...D80A 4P LC1DT60A...DT80A

Dopunske informacije

Lokacija za montiranje	Prednji deo
Način montiranja	Stezaljkom
Tehnologija prigušenja	Dvosmerna dioda za ograničenje napona
Napon upravljačkog kola	126...250 V AC/DC 50/60 Hz
Maksimalni vršni napon	2 Uc
Masa proizvoda	0,02 kg
Boja	Tamnosiva

Okruženje

Standardi	IEC 60947-5-1 EN 60947-5-1 CSA C22.2 No 60947-5-1 UL 60947-5-1 GB/T 14048.5
Sertifikacija proizvoda	UL CSA
Ip stepen zaštite	IP2x u skladu sa IEC 60529
Temperatura okoline za rad uređaja	-25...55 °C
Temperatura okoline za skladištenje	-40...80 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2,0 cm
Package 1 Width	6,0 cm
Package 1 Length	4,0 cm
Package 1 Weight	19,0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	6,5 cm
Package 2 Width	12,0 cm
Package 2 Length	7,0 cm
Package 2 Weight	194,0 g
Unit Type of Package 3	S01

Number of Units in Package 3	100
Package 3 Height	15,0 cm
Package 3 Width	15,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	2,165 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
REACH bez SVHC	Da
EU RoHS direktiva	Usaglašeno EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------