



Osnovne informacije

Grupa proizvoda	Unica
Primena uređaja	Napajanje
Tip proizvoda ili komponente	Utičnica
Ime dekorativnog elementa	Unica (standardna estetika)
Prezentacija uređaja	Mehanizam
Broj utičnica	1
Konfiguracija polova utičnice	2P + E
Standard utičnice	Šuko
Opis standarda utičnice	Uzemljenje sa strane

Dopunske informacije

Tip poklopca	Sa poklopcem
Montaža uređaja	Ugradno
Nazivna struja	16 A
[ue] nazivni napon	250 V
Tip mreže	AC
Mrežna frekvencija	50/60 Hz
Broj modula	2 modula
Način pričvršćivanja	Utično
Nijansa boje	Zelena
Povezivanje - priključci	Priključci bez zavrtnjeva
Poprečni presek kabla	0...4 Mm ² - krutost kabla: fleksibilni 0...4 mm ² - krutost kabla: kruti
Minimalna moć isključenja opterećenja	100 operacija 1.25 In i 1.1 Un, cos phi = 0,6
Električna trajnost	10000 ciklusa, cos phi = 0,8
Otpornost izolacije	> 5 MOhm pri 500 V
Dielektrična snaga	2000 V
Materijal	ASA + PC: mehanizam poklopca
Količina po setu	Set od 1 blister
Sertifikacija proizvoda	FR.ME63.B02375 AC
Dubina za ugradnju	30 mm
Dubina	40 mm
Širina	45 mm
Visina	45 mm

Okruženje

Temperatura okoline za rad uređaja	15...30 °C
Temperatura okoline za skladištenje	0...35 °C
Ik stepen zaštite	IK01
Ip stepen zaštite	IP20
Karakteristike životne sredine	Tečni sapun Aceton Alkohol Benzin Izbeljivač Ulje UV otpornost Tečnost za čišćenje prozora

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,0 cm
Package 1 Width	6,5 cm
Package 1 Length	6,5 cm
Package 1 Weight	34,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4,5 cm
Package 2 Width	13,5 cm
Package 2 Length	33,5 cm
Package 2 Weight	405,0 g
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Height	15,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	1,895 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------