



Osnovne informacije

Range of product	Unica
Ime dekorativnog elementa	Unica Top - Unica Class
Tip proizvoda ili komponente	Taster
Prezentacija uređaja	Mehanizam
Vrsta tehnologije	Elektromehanička
Funkcija prekidača	Jednopolni izborni
Broj prekidača	1
Primena uređaja	Kontrola svetlosti
Nijansa boje	Aluminijum

Dopunske informacije

Nazivna struja	10 A
[ue] nazivni napon	250 V
Tip mreže	AC
Mrežna frekvencija	50/60 Hz
Električna trajnost	40000 ciklusa, $\cos \phi = 0,6$
Otpornost izolacije	> 5 MOhm pri 500 V
Dielektrična snaga	2000 V
Minimalna moć isključenja opterećenja	200 operacija 1.25 In i 1.1 Un, $\cos \phi = 0,3$
Uslovi upotrebe	Kontrola impulsnog releja
Udaljenost otvaranja	> 3 mm
Izvršni organ	Taster
Broj modula	1 modul
Signalna lampica	LED, boja: plava, potrošnja struje: 0.15 mA, porast temperature: 15 °C
Povezivanje - priključci	Priključci bez zavrtnjeva
Poprečni presek kabla	0...2,5 Mm ² kruti kabl 0...2,5 mm ² fleksibilni kabl
Materijal	ASA + PC: mehanizam poklopca ABS (akrilonitril-butadien-stiren): mehanizam poklopca
Način pričvršćivanja	Utično
Širina	22,5 mm
Visina	45 mm
Dubina	34 mm
Dubina za ugradnju	22 mm
Masa proizvoda	0,0193 kg
Temperatura okoline za rad uređaja	25...35 °C
Temperatura okoline za skladištenje	0...50 °C
Standardi	LV direktiva EN 60669-1 EMC direktiva

Okruženje

Ip stepen zaštite	IP20
Ik stepen zaštite	IK01
Karakteristike životne sredine	Benzin Tečnost za čišćenje prozora UV otpornost Izbeljivač Ulje Aceton Alkohol Tečni sapun

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,0 cm
Package 1 Width	6,5 cm
Package 1 Length	6,5 cm
Package 1 Weight	23,11 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4,5 cm
Package 2 Width	13,5 cm
Package 2 Length	33,5 cm
Package 2 Weight	294,5 g
Unit Type of Package 3	S01
Number of Units in Package 3	20
Package 3 Height	15,0 cm
Package 3 Width	15,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	736,0 g

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------