



Osnovne informacije

Range of product	Unica
Ime dekorativnog elementa	Unica Top - Unica Class
Tip proizvoda ili komponente	Taster
Prezentacija uređaja	Mehanizam
Vrsta tehnologije	Elektromehanička
Funkcija prekidača	Jednopolni izborni
Broj prekidača	1
Primena uređaja	Kontrola svetlosti
Nijansa boje	Grafit

Dopunske informacije

Nazivna struja	10 A
[ue] nazivni napon	250 V
Tip mreže	AC
Mrežna frekvencija	50/60 Hz
Električna trajnost	40000 ciklusa, $\cos \phi = 0,6$
Otpornost izolacije	> 5 MOhm pri 500 V
Dielektrična snaga	2000 V
Minimalna moć isključenja opterećenja	200 operacija 1.25 In i 1.1 Un, $\cos \phi = 0,3$
Uslovi upotrebe	Kontrola impulsnog releja
Udaljenost otvaranja	> 3 mm
Izvršni organ	Taster
Broj modula	2 modula
Signalna lampica	LED, boja: plava, potrošnja struje: 0.15 mA, porast temperature: 15 °C
Povezivanje - priključci	Priključci bez zavrtnjeva
Poprečni presek kablova	0...2,5 Mm ² kruti kabl 0...2,5 mm ² fleksibilni kabl
Materijal	ABS (akrilonitril-butadien-stiren): mehanizam poklopca
Označavanje	OFF
Način pričvršćivanja	Utično
Širina	45 mm
Visina	45 mm
Dubina	34 mm
Dubina za ugradnju	22 mm
Masa proizvoda	0,0226 kg
Temperatura okoline za rad uređaja	25...35 °C
Temperatura okoline za skladištenje	0...50 °C
Standardi	EN 60669-1 LV direktiva EMC direktiva

Okruženje

Ip stepen zaštite	IP20
Ik stepen zaštite	IK01
Karakteristike životne sredine	Tečnost za čišćenje prozora Ulje Alkohol Tečni sapun UV otpornost Benzin Izbeljivač Aceton

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,5 cm
Package 1 Width	6,6 cm
Package 1 Length	6,7 cm
Package 1 Weight	26,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	14,0 cm
Package 2 Width	5,0 cm
Package 2 Length	34,0 cm
Package 2 Weight	333,0 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	4,483 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------