



Osnovne informacije

Grupa proizvoda	Unica
Primena uređaja	Upravljanje
Tip proizvoda ili komponente	Kontrola zatvarača
Ime dekorativnog elementa	Unica Top - Unica Class
Prezentacija uređaja	Mehanizam
Nazivna struja	10 A
[ue] nazivni napon	250 V
Tip mreže	AC
Mrežna frekvencija	50/60 Hz
Način pričvršćivanja	Utično
Nijansa boje	Grafit

Dopunske informacije

Montaža uređaja	Ugradno
Broj modula	2 modula
Vrsta tehnologije	Elektromehanička
Izvršni organ	Preklopni prekidač
Broj prekidača	2
Funkcija prekidača	Jednopolni naizmjenični
Primena prekidača	Roletne
Tip kontakata i sastav	1 C/O
Mehanička blokada	Blokada između funkcija nagore/nadole
Nazivna struja prekida	2,5 A za motor
Udaljenost otvaranja	> 3 mm
Označavanje	Nadole UP
Povezivanje - priključci	Priključci bez zavrtnjeva
Poprečni presek kabla	2,5 mm ² fleksibilni kabl 2,5 mm ² kruti kabl
Minimalna moć isključenja opterećenja	200 operacija 1.25 In i 1.1 Un, cos phi = 0,3
Električna trajnost	40000 ciklusa, cos phi = 0,6
Otpornost izolacije	> 5 MOhm pri 500 V
Dielektrična snaga	2000 V
Materijal	ABS (akrilonitril-butadien-stiren): mehanizam poklopca
Standardi	EN 60669-1 EMC direktiva LV direktiva
Temperatura okoline za rad uređaja	25...35 °C
Temperatura okoline za skladištenje	0...50 °C
Dubina za ugradnju	22 mm
Dubina	34 mm
Širina	45 mm
Visina	45 mm
Masa proizvoda	0,0351 kg

Okruženje

Ik stepen zaštite	IK01
Ip stepen zaštite	IP20
Karakteristike životne sredine	Tečni sapun UV otpornost Aceton Benzin Izbeljivač Tečnost za čišćenje prozora Ulje Alkohol

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,0 cm
Package 1 Width	6,5 cm
Package 1 Length	6,5 cm
Package 1 Weight	38,3 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	4,5 cm
Package 2 Width	13,5 cm
Package 2 Length	33,5 cm
Package 2 Weight	450,0 g
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Height	15,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	2,034 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	 REACH Deklaracija
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------