



Osnovne informacije

Grupa proizvoda	Unica
Tip proizvoda ili komponente	Potezni prekidač
Ime dekorativnog elementa	Unica (standardna estetika)
Prezentacija uređaja	Mehanizam
Primena uređaja	Upravljanje
Funkcija prekidača	Jednopolni izborni
Nazivna struja	10 A
Izvršni organ	Potezni taster
Broj modula	2 modula
Način pričvršćivanja	Utično
Nijansa boje	Bela (RAL 9003)

Dopunske informacije

Vrsta tehnologije	Elektromehanička
Dužina kabla	1 m
[ue] nazivni napon	250 V
Tip mreže	AC
Mrežna frekvencija	50/60 Hz
Udaljenost otvaranja	> 3 mm
Povezivanje - priključci	Priključci bez zavrtnjeva
Poprečni presek kabla	2,5 Mm ² fleksibilni kabl 2,5 mm ² kruti kabl
Minimalna moć isključenja opterećenja	200 operacija 1.25 In i 1.1 Un, cos phi = 0,3
Električna trajnost	40000 ciklusa, cos phi = 0,6
Dielektrična snaga	2000 V
Otpornost izolacije	> 5 MOhm pri 500 V
Materijal	ASA + PC: mehanizam poklopca
Standardi	LV direktiva EN 60669-1 EMC direktiva
Temperatura okoline za rad uređaja	25...35 °C
Temperatura okoline za skladištenje	0...50 °C
Dubina za ugradnju	22 mm
Dubina	34 mm
Širina	45 mm
Visina	45 mm
Masa proizvoda	0,0291 kg

Okruženje

Ik stepen zaštite	IK01
Ip stepen zaštite	IP20
Karakteristike životne sredine	Ulje Alkohol Tečnost za čišćenje prozora UV otpornost Aceton Izbeljivač Tečni sapun Benzin

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4,0 cm
Package 1 Width	5,0 cm
Package 1 Length	7,0 cm
Package 1 Weight	30,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	12,7 cm
Package 2 Width	12,4 cm
Package 2 Length	18,5 cm
Package 2 Weight	374,0 g
Unit Type of Package 3	S02
Number of Units in Package 3	40
Package 3 Height	15,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	1,814 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACh	 REACh Deklaracija
REACh bez SVHC	Da
EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	 Profil Ekološke Prihvatljivosti Proizvoda
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------