



Osnovne informacije

Grupa proizvoda	Unica
Ime dekorativnog elementa	Unica Top - Unica Class
Tip proizvoda ili komponente	Komunikacione utičnice
Primena uređaja	Komunikacija
Prezentacija uređaja	Mehanizam
Nijansa boje	Aluminijum
Tip komunikacione utičnice	RJ45 4 kontakt(i) kat.6 < 250 MHz
Zaštitna oprema	Nosač oznake Zaštitni poklopac

Dopunske informacije

Tip komunikacione mreže	1000BASE-TX
Protokol komunikacionog porta	ATM 1200 Mbps
Namena proizvoda	Podna kutija Kablovski vod
Broj modula	1 modul
Broj utičnica	1
Tip dizajna	Infraplus
Tip priključka	S-One
Tip oklopa kabla	S/FTP
Način formiranja kabla	Oklopljen kabl sa upredenim paricama
Povezivanje - priključci	Na klik
Montaža uređaja	Ugradno
Način fiksiranja	Utično Stezaljka: oklop
Pravac instalacije	Ravno
Materijal	ABS (akrilonitril-butadien-stiren): mehanizam poklopca
Dubina	36 mm
Širina	22,5 mm
Visina	45 mm
Dubina za ugradnju	25 mm

Okruženje

Ip stepen zaštite	IP40
Ik stepen zaštite	IK01
Temperatura okoline za rad	15...30 °C
Temperatura okoline za skladištenje	0...35 °C
Karakteristike životne sredine	Aceton Tečni sapun Alkohol Tečnost za čišćenje prozora Izbeljivač Benzin Ulje UV otpornost
Standardi	ISO 8877

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3,0 cm
Package 1 Width	5,0 cm
Package 1 Length	5,0 cm
Package 1 Weight	43,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	5,7 cm
Package 2 Width	11,0 cm
Package 2 Length	24,5 cm
Package 2 Weight	491,0 g
Unit Type of Package 3	S02
Number of Units in Package 3	60
Package 3 Height	15,0 cm
Package 3 Width	30,0 cm
Package 3 Length	40,0 cm
Package 3 Weight	3,256 kg

Održivost ponude

EU RoHS direktiva	Usaglašeno  EU RoHS Deklaracija
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	 Da
RoHS regulativa za Kinu	 RoHS Deklaracija Za Kinu
WEEE	Ovaj proizvod je na tržištima Evropske unije neophodno odložiti u skladu sa specifičnim smernicama za prikupljanje otpada i nikako ne sme da dospe u kontejnere za otpatke.

Ugovorna garancija

Garancija	18 meseci
-----------	-----------