



Osnovne informacije

Grupa proizvoda	Resi9
Ime proizvoda	Resi9 MP
Tip proizvoda ili komponente	Orman
Tip ormara	Modularni orman
Nb of 18 mm modules per row	4
Nb of horizontal rows	1
Type of door	Puni
Širina	126 Mm zid: 150 mm spoljašnja strana:
Visina	228 Mm zid: 252 mm spoljašnja strana:
Dubina	18 Mm spoljašnja strana: 80 Mm zid: 98 mm ukupno:

Dopunske informacije

Montaža ormara	Ugradna
9 mm redovi	8
Ukupan broj 18 mm modula	4
[in] nazivna struja	50 A
Tip šine	35 mm asimetrična šina
Opis montažne ploče	Bez montažne ploče
Kablovski uvod	Predefinisani otvori
Funkcija priključnog bloka	Uzemljenje/nula
Broj priključnih blokova	1 uzemljenje (vijčano) sa 4 izvodi 1 nula (vijčano) sa 4 izvodi
Izvodi razvodnog bloka	1 x 16 mm ² za uzemljenje 1 x 16 mm ² za nula 1 x 6 mm ² za uzemljenje 1 x 6 mm ² za nula 2 x 10 mm ² za uzemljenje 2 x 10 mm ² za nula
Materijal kućišta	Zadnji deo: tehno plastika Vrata: tehno plastika Prednja strana: tehno plastika
Unutrašnja dubina	76 mm
Boja	Vrata: bela (RAL 9003) Prednja strana: bela (RAL 9003)
Segment tržišta	Stambene zgrade Male komercijalne zgrade

Okruženje

Standardi	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
Oznake kvaliteta	IMQ
Otpornost na vatru	Vrata: 650 °C Zadnji deo: 650 °C Prednja strana: 650 °C
Ip stepen zaštite	IP40
Ik stepen zaštite	IK07
Temperatura okoline za rad uređaja	-25...60 °C

Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9,5 cm
Package 1 Width	15,0 cm
Package 1 Length	25,0 cm
Package 1 Weight	496,0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	15
Package 2 Height	53,0 cm
Package 2 Width	31,0 cm
Package 2 Length	41,0 cm
Package 2 Weight	8,076 kg
Unit Type of Package 3	P12
Number of Units in Package 3	240
Package 3 Height	118,5 cm
Package 3 Width	80,0 cm
Package 3 Length	120,0 cm
Package 3 Weight	141,208 kg

Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	REACH Deklaracija
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS) EU RoHS deklaracija
Bez žive	Da
Informacije o RoHS izuzecima	Da
RoHS regulativa za Kinu	RoHS Deklaracija Za Kinu
Izjava o zaštiti okoliša	Profil Ekološke Prihvatljivosti Proizvoda
Učinak u vezi sa sadržajem halogena	Proizvod bez halogena

Ugovorna garancija

Garancija	18 months
-----------	-----------