

# Tehničke karakteristike proizvoda

## Karakteristike

# NSYTBS342916H

ABS kutija IP66 IK07 RAL7035

U:V325Š275D160 S:V341Š291D168 neprov.  
poklopac V60



## Osnovne informacije

Grupa proizvoda	Thalassa
Ime proizvoda	Thalassa TBS
Primena uređaja	Više namena
Category	Industrijska kutija
Visina	341 mm
Širina	291 mm
Dubina	168 mm
Unutrašnja visina	325 mm
Unutrašnja širina	275 mm
Unutrašnja dubina	160 mm
Montaža ormara	Montaža na zid
Sastav uređaja	1 telo 1 poklopac 4 zavrtnaj poklopca
Tip kućišta	Izliveno iz jednog dela
Tip prednjeg poklopca	Visoki puni poklopac
Fiksiranje poklopca	Plastični zavrtnji
Tip brave	Neodvojiv zavrtnaj ravan spoljašnja zaptivena oblast
Odvojivi delovi	Poklopac sa neodvojivim zavrtnjima

## Dopunske informacije

Materijal	ABS (akrilonitril-butadien-stiren)
Boja	Siva (RAL 7035)
Standardi	IEC 62208
Sertifikacija proizvoda	TÜV
Električna klasa izolacije	Klasa II
Ip stepen zaštite	IP66 u skladu sa NEMA 4.4X
Ik stepen zaštite	IK07 u skladu sa IEC 62262
Glow wire resistance	650 °C u skladu sa IEC 60695-2-11
Temperatura okoline za skladištenje	-15...40 °C
Operating temperature	-25...60 °C
Masa proizvoda	1,66 kg

## Pakovanje

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18,5 cm
Package 1 Width	30 cm
Package 1 Length	36 cm
Package 1 Weight	1,63 kg
Unit Type of Package 2	CAR
Number of Units in Package 2	3
Package 2 Height	40 cm
Package 2 Width	40 cm
Package 2 Length	60 cm

Package 2 Weight	5,88 kg
Unit Type of Package 3	P12
Number of Units in Package 3	36
Package 3 Height	136 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	79 kg

## Održivost ponude

Status održive ponude	Green Premium proizvod
Propis REACH	<a href="#">REACH Deklaracija</a>
REACH bez SVHC	Da
EU RoHS direktiva	Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS) <a href="#">EU RoHS deklaracija</a>
Bez toksičnih teških metala	Da
Bez žive	Da
Informacije o RoHS izuzecima	<a href="#">Da</a>
RoHS regulativa za Kinu	<a href="#">RoHS Deklaracija Za Kinu</a>
Izjava o zaštiti okoliša	<a href="#">Profil Ekološke Prihvatljivosti Proizvoda</a>

## Ugovorna garancija

Garancija	18 months
-----------	-----------