



## Osnovne informacije

|                                |                          |
|--------------------------------|--------------------------|
| Tip proizvoda ili komponente   | Motorna prigušnica       |
| Kompatibilnost grupe proizvoda | Altivar 71<br>Altivar 61 |
| Specifične primene proizvoda   | Izlazni filter           |
| [in] nazivna struja            | 48 A                     |

Kompatibilnost  
proizvoda

ATV61H075N4  
ATV61HU15N4  
ATV61HU22N4  
ATV61HU30N4  
ATV61HU40N4  
ATV61W075N4  
ATV61W075N4C  
ATV61WU15N4  
ATV61WU15N4C  
ATV61WU22N4  
ATV61WU22N4C  
ATV61WU30N4  
ATV61WU30N4C  
ATV61WU40N4  
ATV61WU40N4C  
ATV71H075N4  
ATV71HU15N4  
ATV71HU22N4  
ATV71HU30N4  
ATV71HU40N4  
ATV71P075N4Z  
ATV71PU15N4Z  
ATV71PU22N4Z  
ATV71PU30N4Z  
ATV71PU40N4Z  
ATV71W075N4  
ATV71WU15N4  
ATV71WU22N4  
ATV71WU30N4  
ATV71WU40N4  
ATV61HD11N4  
ATV61HD11Y  
ATV61HD15N4  
ATV61HD18N4  
ATV61HU22S6X  
ATV61HU30M3  
ATV61HU30S6X  
ATV61HU30Y  
ATV61HU40M3  
ATV61HU40S6X  
ATV61HU40Y  
ATV61HU55M3  
ATV61HU55N4  
ATV61HU55S6X  
ATV61HU55Y  
ATV61HU75M3  
ATV61HU75N4  
ATV61HU75S6X  
ATV61HU75Y  
ATV61WD11N4  
ATV61WD11N4C  
ATV61WD15N4  
ATV61WD15N4C  
ATV61WD18N4  
ATV61WD18N4C  
ATV61WU55N4  
ATV61WU55N4C  
ATV61WU75N4  
ATV61WU75N4C  
ATV71HD11N4  
ATV71HD11Y  
ATV71HD15N4  
ATV71HD18N4  
ATV71HU15S6X  
ATV71HU22S6X  
ATV71HU22Y  
ATV71HU30M3  
ATV71HU30S6X  
ATV71HU30Y  
ATV71HU40M3  
ATV71HU40S6X  
ATV71HU40Y  
ATV71HU55M3  
ATV71HU55N4  
ATV71HU55S6X  
ATV71HU55Y  
ATV71HU75M3  
ATV71HU75N4  
ATV71HU75S6X  
ATV71HU75Y  
ATV71PD11N4Z  
ATV71PU55N4Z  
ATV71PU75N4Z  
ATV71WD11N4  
ATV71WD15N4

|                   |  |
|-------------------|--|
| Potrebna količina | 1  |
| Električna veza   | Priključak, kapacitet priključka: 10 mm <sup>2</sup> / AWG 6 |

## Dopunske informacije

|                                       |   |
|---------------------------------------|---|
| Maksimalna dužina kabla motora        | 200 M oklopljen kabl P motora 2,2...7,5 kW pri 200...240 V 1<br>260 M neoklopljen kabl P motora 2,2...7,5 kW pri 200...240 V 1<br>85 M oklopljen kabl P motora 0,75...18,5 kW pri 380...480 V 1<br>95 M neoklopljen kabl P motora 0,75...18,5 kW pri 380...480 V 1<br>50 M oklopljen kabl P motora 2,2...7,5 kW pri 500...600 V 1<br>100 M neoklopljen kabl P motora 2,2...7,5 kW pri 500...600 V 1<br>45 M oklopljen kabl P motora 2,2...11 kW pri 500...690 V 1<br>70 m neoklopljen kabl P motora 2,2...11 kW pri 500...690 V 1 |
| Dv/dt                                 | 500 V/μs maksimalno pri 400 V<br>750 V/μs maksimalno pri 500 V<br>1000 V/μs maksimalno pri 690 V  |
| Termički gubici                       | 250 W   |
| Moment pritezanja                     | 1,5 N.m   |
| Maksimalna izlazna frekvencija pogona | 100 Hz  |
| Tip zaštite                           | Termička zaštita sa temperaturno kontrolisan prekidač, temperatura prorade zaštite: 125 °C za <250 V AC, <0,5 A   |
| Temperatura okoline za rad            | -10...50 °C   |
| Masa proizvoda                        | 8 kg  |





## Okruženje

|                                     |   |
|-------------------------------------|---|
| Ip stepen zaštite                   | IP20 (sa setovima VW3A9612,613)<br>IP00 |
| Temperatura okoline za skladištenje | -25...70 °C                             |

## Pakovanje

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 26,5 cm  |
| Package 1 Width              | 27,1 cm  |
| Package 1 Length             | 28,1 cm  |
| Package 1 Weight             | 5,979 kg |
| Unit Type of Package 2       | S06      |
| Number of Units in Package 2 | 12       |
| Package 2 Height             | 74,0 cm  |
| Package 2 Width              | 60,0 cm  |
| Package 2 Length             | 80,0 cm  |
| Package 2 Weight             | 85,0 kg  |

## Održivost ponude

|                              |  |
|------------------------------|--|
| Propis REACH                 |  <a href="#">REACH Deklaracija</a>  |
| REACH bez SVHC               | Da   |
| EU RoHS direktiva            | Proaktivna usaglašenost (proizvod nije u zakonskom okviru direktive EU RoHS)  <a href="#">EU RoHS deklaracija</a> |
| Bez toksičnih teških metala  | Da   |
| Bez žive                     | Da   |
| Informacije o RoHS izuzecima |  Da   |
| RoHS regulativa za Kinu      |  <a href="#">RoHS Deklaracija Za Kinu</a>   |

## Ugovorna garancija

|           |           |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|