

Montaž kit 290ml

Opis proizvoda

Montaž kit je materijal za vezivanje i popunjavanje, na bazi sintetičke gume/smole velike jačine i razređivača.

Svojstva

Formula na bazi razređivača što omogućava brzo sušenje i brzo, snažno vezivanje

- Odlično prijanja na većinu građevinskih materijala
- Izuzetna svojstva brzog vezivanja – primenjuje se i za horizontalne i za vertikalne radove
- Odlično ispunjava pukotine, bez skupljanja
- Primenljivo i kada su obe površine neporozne
- Odlična otpornost na spoljne uticaje – koristi se za spoljašnje radove
- Proizvod nije namenjen da se koristi sa sledećim materijalima: polistirenom, polipropilenom, polietilenom i teflonom.

Tehnički podaci

Hemijska baza: Mix gume/smole

Izgled: Pasta

Specifična težina: 1,24 +/-0,03 g/cm³ (DIN 53479)

Momentalno vezivanje: <30 sekundi (+250C i 50% R.H.)

Otpornost na istezanje: 5 N/mm²

Gubitak zapremine: 27% (ASTM D 53505)

Detalji o primeni

Temperatura prilikom pripreme: +50°C do +350°C

Otporno na temperature: -400°C do +900°C

Jednostavno za primenu. Brzo se suši. Posebno pogodno za fiksiranje različitih predmeta od kamena, betona, keramike, cigle, plastike, PVC, drveta, panela...

Pakovanje

290 ml – 290 ml x 25 boca u kutiji

Boja

Bež

Rok trajanja

Skladištiti u suvim uslovima, zaštićeno od direktnog uticaja sunca.

Rok upotrebe 12 meseci na temperaturi +50°C do +250°C.

Oznake rizika

Čuvati van domašaja dece. Izbegavati kontakt sa kožom i očima. Koristiti u dobro provetrenim prostorima. Ne udisati isparenja. Zabranjeno pušenje za vreme korišćenja proizvoda.

Oznake bezbednosti

Za više informacija i saveta vezano za bezbedno korišćenje, skladištenje i odlaganje, korisnici treba da koriste najnoviji Bezbednosni list.



šifra: MNK
barkod: 8606007997576

šifra: MNKT
barkod: 8606107779935

Montage kit 290ml

Product Description

The mounting kit is a bonding and filling material, based on high-strength synthetic resins / resins and thinners.

Properties

Thinner-based formula that allows for quick drying and fast, strong bonding

- Excellent adhesion to most building materials
- Exceptional fast setting properties - applies to both horizontal and vertical work
- Perfectly fills cracks, without shrinkage
- Also applicable when both surfaces are non-porous
- Excellent resistance to external influences - used for external works
- The product is not intended to be used with the following materials: polystyrene, polypropylene, polyethylene and Teflon.

Technical Information

Chemical base: Rubber / resin mix

Appearance: Pasta

Specific gravity: 1.24 +/- 0.03 g / cm³ (DIN 53479)

Instant setting: <30 seconds (+ 250C and 50% RH)

Tensile strength: 5 N / mm²

Volume loss: 27% (ASTM D 53505)

Application Details

Temperature during preparation: + 50°C to + 350°C

Temperature resistant: -400°C to + 900°C

Easy to apply. It dries quickly. Especially suitable for fixing various objects made of stone, concrete, ceramics, brick, plastic, PVC, wood, panels...

Packaging

290 ml - 290 ml x 25 bottles in a box

Color

Beige

Shelf Life

Store in dry conditions, protected from direct sunlight.

Shelf life 12 months at temperatures + 50°C to + 250°C.

Risk labels

Keep out of reach of children. Avoid contact with skin and eyes.

Use in well-ventilated areas. Do not breathe vapor. No smoking while using the product.

Health and Safety

For more information and advice on safe use, storage and disposal, users should use the latest Safety Data Sheet.



code: MNK
barcode: 8606007997576

code: MNKT
barcode: 8606107779935