

Antikorozivni sprej

Datum: decembar 2014

Svojstva i oblasti upotrebe

Pružna metalnim površinama trajnu zaštitu od rđe.

Može se prefarbati originalnom bojom, ali tek nakon što se prvi sloj osuši.

Akrične smole koje sadrže čine ga pogodnim za unutrašnju i spoljašnju upotrebu, garantujući otpornost na atmosferske uticaje.

Specifikacija pakovanja

Boca obložena folijom od 15 bara

Neto sadržaj

400 ml

Izgled

Boca koja sadrži tečnost pod pritiskom

Boja

Razne

Miris

Tipičan rastvarač

Gustina na 20°C

0.75 - 0.80 g/ml

Pritisak na 20°C

4.0 ± 0.5 bar

Pritisak na 50°C

8.0 ± 0.5 bar

Tačka zapaljivosti

Manje od 0° C

Viskozitet Ford Cup 4

11,4"

Preostali suvi cilindar

21,50%

Grit to grindometro

Od 0 do 2 Micron

Sjaj

Od 25 do 30 sjaja

Gustina 1 ruka

13 Micron

Gustina 3 ruke

35 Micron

Otpornost na temperaturu

100 - 120°C

Vreme sušenja:

Otpornost na prašinu

10 minuta

Suvo na dodir

20 minuta

Potpuno suvo

24 sata

Može se prefarbati u bilo kom trenutku

Patentirana sigurnosna kapa zaštićena od dece

Referentni flaster u boji

Etiketiranje



šifra: SAKS
barkod: 8606017650355

Rust proofing spray paint

Date: December 2014

Properties and areas of use

Offers metal surfaces lasting protection against rust.
It can be painted over with the original paint, but only after the first coat has dried.
The acrylic resins contained make it suitable for indoor and outdoor use, guaranteeing resistance against atmospheric agents.

Supply specifications

15 bar foil-coated can	
Net content	400 ml
Appearance	Can containing pressurised liquid
Colour	Miscellaneous
Scent	Typical solvent
Density at 20°C	0.75 - 0.80 g/ml
Pressure at 20°C	4.0 ± 0.5 bar
Pressure at 50°C	8.0 ± 0.5 bar
Flammability point	less than 0° C
Viscosity Ford Cup 4	11,4"
Remaining dry cylinder	21,50%
Grit to grindometro	From 0 to 2 Micron
Gloss	From 25 to 30 Gloss
Thickness 1 hand	13 Micron
Thickness 3 hands	35 Micron
Temperature resistance	100 - 120°C
Drying time:	
Dust resistant	10 minutes
Dry to touch	20 minutes
Fully dry	24 hours

May be painted over at any time
Childproof patented safety cap
Colour reference patch

Labelling



code: SAKS
barcode: 8606017650355