

Lak bezbojni sjajni Transparent

Svojstva i oblasti upotrebe

Prozirni akrilni lak koji nudi odličnu adheziju na metale.

Štiti ih od atmosferskih uticaja, zadržavajući njihov prvobitni izgled.

Pogodan i za zaštitu ukrasa, keramičkih, drvenih i plastičnih predmeta.

Limenka od 400 ml pokriva površinu od 1,5 - 2 m², u zavisnosti od vrste elementa koji se farba.

Specifikacija pakovanja

Boca obložena folijom od 15 bara

Neto sadržaj

400 ml

Izgled

Boca koja sadrži tečnost pod pritiskom

Boja

Razne

Miris

Tipičan rastvarač

Gustina na 20°C

0.75 - 0.80 g/ml

Pritisak na 20°C

4.0 ± 0.5 bar

Pritisak na 50°C

8.0 ± 0.5 bar

Tačka zapaljivosti

Manje od 0° C

Viskozitet Ford Cup 4

11"

Preostali suvi cilindar

14.8%

Grit to grindometro

0 Micron

Sjaj

90 sjaja

Gustina 1 ruka

5 Micron

Gustina 3 ruke

15 Micron

Otpornost na temperaturu

100-120°C

Vreme sušenja:

Otpornost na prašinu

10 minuta

Suvo na dodir

20 minuta

Potpuno suvo

24 sata

Može se prefarbati u bilo kom trenutku

Patentirana sigurnosna kapa zaštićena od dece

Referentni flaster u boji

Etiketiranje



Datum: februar 2015

šifra: SLBS
barkod: 8606017650287

šifra: SLBM
barkod: 8606017650294

Wanish spray glossy, Transparente

Properties and areas of use

Clear acrylic varnish offering excellent adhesion to metals. It protects them against atmospheric agents, maintaining their original appearance. Also suitable for protecting ornaments, ceramic, wooden and plastic objects. The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

Supply specifications

15 bar foil-coated can	
Net content	400 ml
Appearance	Can containing pressurised liquid
Colour	Miscellaneous
Scent	Typical solvent
Density at 20°C	0.75 - 0.80 g/ml
Pressure at 20°C	4.0 ± 0.5 bar
Pressure at 50°C	8.0 ± 0.5 bar
Flammability point	less than 0° C
Viscosity Ford Cup 4	11"
Remaining dry cylinder	14.8%
Grit to grindometro	0
Gloss	90 Gloss
Thickness 1 hand	5 Micron
Thickness 3 hands	15 Micron
Temperature resistance	100-120°C
Drying time:	
Dust resistant	10 minutes
Dry to touch	20 minutes
Fully dry	24 hours

May be painted over at any time
 Childproof patented safety cap
 Colour reference patch

Labelling



Date: February 2015

code: SLBS
 barcode: 8606017650287

code: SLBM
 barcode: 8606017650294